

Python® III Dash-Mount Radar System

POLICE RADAR · POLICE LASERS · SURVEY LASERS · SPEED SIGNS

A Classic Design

The classic Python radar system has been completely designed with the user in mind. The smaller readout unit has a completely new look with bigger, easier-to-read displays. The K-band antenna unit is the smallest of its kind on the market. The simple remote control allows you to keep your eyes on the road instead of looking for buttons. The Python III accepts a speedometer interface module, the only one that doesn't force you to modify your cruiser. Simply the best basic radar package available and priced to fit your budget.



enefits
,

Smaller readout with larger displays	Easy-to-read while taking less dash space.
Smaller K-band antenna	More flexibility of mounting locations.
Uncluttered remote control	Easier operation without taking your eyes off the road.
Intuitive roadway-style mode display	Graphically displays the current operating mode.
X, K and Ka-band versions	Options to choose the band that's right for you.
Same display configuration as BEE III™	Simplifies your operator training programs.
Optional same direction & fastest modes	Add features as your needs evolve.
Optional speedometer interface	Eliminate false patrol speed readings, with no modifications to vehicle.
Software upgradable through data port	Easily add features or updates as needed.





Description: The Python Series III moving radar is designed for convenient use by law enforcement agencies in measuring the speed of vehicles. Available in X, K or Ka-band, the Python III operates from stationary or moving patrol vehicles, using the well known and legally accepted Doppler principle. The radar has been type accepted by the Federal Communications Commission and conforms to all NHTSA specifications.

Special Features

- Python utilizes true Digital Signal Processing (DSP), allowing it to monitor all targets in the radar beam simultaneously. Inferior techniques, which are simply advanced analog processing methods masquerading as DSP, cannot match the performance of the Python.
- Python is simple yet effective. No other moving radar can match the simplicity of the Python's design. The remote control can easily be operated while the user focuses on the road. The pushbuttons on the readout unit are clearly labeled and can be operated with gloved hands.
- Python uses MPH's exclusive high-quality Doppler audio. This court-proven feature is a true indicator of the quality of the target's return signal. The volume increases when the signal strength increases, and any interfering targets that are present become immediately apparent.
- The reliability and accuracy of the Python are guaranteed by MPH Industries. The Python conforms to NHTSA radar specifications.
- Python contains the following functions and controls:
 Power Range Control Antenna Select
 Test Moving/Stationary Volume Control
 Squelch Patrol Blanking Antenna Standby
 RFI Detect Low Voltage Sensing Lock/Release
 RS-232 Communication Port

General Specifications

• Power: 10.8 to 16.5 Volts DC, 0.9 Amps @ 13.6 V nominal. Fused power cable. Reverse polarity protection.

 Operating modes and speed ranges: The basic Python Series III is equipped with stationary mode and opposite-direction moving mode software. As an option, you may purchase the "FS" version of the radar, which adds fastest vehicle mode and same direction moving mode. Both versions are equipped with a City/Highway mode to minimize patrol speed errors in low speed and highway speed conditions.

Both versions also accept MPH's speedometer interface module. The module receives approximate vehicle speed information from the patrol vehicle and uses it to help the radar interpret the correct patrol speed. When in use the radar's City/Highway mode is selected automatically by the radar, based on the speedometer reading. The Python is also capable of higher patrol speeds when the speedometer interface is in use.

· Target Distance:

Typically, one mile range for the average size vehicle. Range can vary with vehicle size, terrain, weather and traffic conditions.

· Speed Display:

Three LED windows simultaneously display patrol, target, and locked speeds. Display brightness automatically adjusts to the ambient light level. All displays are 0.4 inches in height.

Readout Unit Size:

1.6" H x 6.5" W x 4.9" D

· Antenna (K-band):

Modules consist of a circularly polarized, seamless conical horn antenna and shatterproof microwave lens, contained in a rugged

cylindrical aluminum housing.

Antenna (Ka-band):

Frequency: 33.8GHz + 100 MHz (Ka-band)

Type: Circularly polarized, with seamless conical horn and Rexolite

microwave lens.

Enclosure: All-aluminum housing with a waterproof polycarbonate radome

cover incorporating O-ring seals.



The MPH Python III is manufactured in our Owensboro, KY facility and is in compliance with the BUY AMERICA ACT.

For more information or official documentation, contact us at www.mphindustries.com

MPH Industries, Inc.

316 East 9th Street
Owensboro, KY 42303
www.mphindustries.com
info@mphindustries.com
888-689-9222